

# ROLLOVER

THE ART OF LAMINATING



## Delivery Requirements Rollover® Flatbed Applicators

- **Truck Delivery (1)**   
Applicator **CAN NOT** be off loaded with a liftgate due to the length of the unit
- **Forklift Required (2)**   
Forklift must have long forks
- **Compressed Air (3)**   
Dry clean air  
Minimum of 6 bar/87 psi-from a small compressor or inhouse supply line  
Compressor is NOT included with the purchase
- **Doorways (4)** 
  - **Vertical Transport**

***Rollover Flexi Vertical Device: Min. width of door opening 30'' (legs taken off)***

***Rollover Classic Vertical Device: Min. width of door opening 32'' (28'' without castors)***

**(1)** If customer has a dock the Applicator can be pulled out from the back of the truck. It is best to have a forklift with long forks due to the length of the unit. If there is no dock the Applicator can be off loaded with a forklift but must have long forks due to the length of the unit. Please note if the customer has a place to store the Applicator in a dry area until time of installation and will have forklift available with long forks at time of installation. You will also need to check if the access to the building is suited for the truck arrival and if there are any obstacles like steps, ramps, etc. that needs to be considered.

# ROLLOVER

THE ART OF LAMINATING

- (2) The Applicator arrives in a large wooden crate. At time of installation the crate will need to be disassembled and the Applicator will need to be lifted from the center in order to remove Applicator from the bottom crate. A forklift with long forks will be REQUIRED for this step of the process.
- (3) Unit comes with a female quick disconnect adapter. End user will need to supply clean dry air supply with male quick disconnect adapter. If they prefer a stand-alone compressor at the Applicator it should be one with a ultra quiet decibel noise rating.

Below are two suggested suppliers:

## **Home Depot**

California Air Tools – Ultra Quiet

Minimum of a two gallon tank preferred.

These must be ordered from their website as they are not available at your local store locations.

## **Harbor Freight**

Fortress – Ultra Quiet

Minimum of a two gallon tank preferred.

Normally in stock at local store locations.

- (4) Please review and measure all doorways and hallways from delivery point to the final Applicator location. Applicator is supplied with casters and can be rolled into position after uncrating if all doorways are the width of the Applicator. If going down a hallway, please make sure that the Applicator is able to be turned in all directions due to the long length to the final location. The applicator can be rotated on its' side for narrow entrance ways with a Vertical Transport Device. The Vertical Transport Device can be rented for the cost of \$200 plus the cost of truck shipping to and from the location. Please review that there are no steps from beginning to end point of the Applicator.

# ROLLOVER

THE ART OF LAMINATING

## **INSTALLATION NOTES:**